

Liesegang



ohp 3010 – Reliable and low cost, suited for daily use.

ohp 3510 – For bigger rooms and larger audiences.

The Liesegang projector ohp 3010 has received design awards for all standard requirements and complements ideally our multimedia projectors.

The Liesegang projector ohp 3510. Its brightness ensures an optimum of brilliance of the projected images, even at sunlight.



ohp 3010
ohp 3510

ohp 3010 ohp 3510



- High-end lens
- Special coating
- Power saving switch
- Quick lamp changer
- Foldable projection column

Liesegang ohp 3010

Lens f = 12.4 in. (315 mm)

Accessories for Liesegang ohp 3010

Scroll attachment

Foil roll, 32.8 ft (10 m)

Foil roll, 98.4 ft (30 m)

100 A4 transparencies

Projection cart, working height infinitely adjustable
approx. 29.92 - 39.76 in. (760 - 1010 mm)

(with additional plate only)

additional plate required for ohp 3010

Spare lamp 24V/250 Watt/Type 310

0672 315 00000

ZU0670 71 0000

ZU0601 40 4200

ZU0601 40 4220

ZU0601 40 4010

ZU0625 78 000G

ZU0630 74 0000

ZU0310 05 2200

Liesegang ohp 3510

Lens f = 12.4 in. (315 mm)

Accessories for Liesegang ohp 3510

Scroll attachment

Foil roll, 32.8 ft (10 m)

Foil roll, 98.4 ft (30 m)

100 A4 transparencies

Projection cart, working height infinitely adjustable
approx. 29.92 - 39.76 in. (760 - 1010 mm)

(with additional plate only)

additional plate required for ohp 3510

Spare lamp 36 V/400 Watt/Type 610

0674 315 00000

ZU0670 71 0000

ZU0601 40 4200

ZU0601 40 4220

ZU0601 40 4010

ZU0625 78 000G

ZU0630 74 0000

ZU0610 02 2040

Technical Data	ohp 3010	ohp 3510
Desktop	•	•
Can be integrated	—	—
Foldable column	•	•
Portable hydraulic column	—	—
Focus control	—	—
Lamp/Power		
Low-voltage halogen lamp	250 Watt	400 Watt
Quick lamp changer	•	•
Lifetime of lamp	up to 50 hrs	up to 50 hrs
Brightness (ANSI lumens)	2000 lm	3500 lm
Power save function	•	•
Equipment		
Anti-glare foldable fresnel lens	—	—
Anti-glare removable fresnel lens	•	•
Condensor lens with cold-light mirror	—	—
Color fringe correction	—	—
Plug for additional units	—	—
Pen holder	—	—
Submersible clips for single transparencies	•	•
Scroll cassette	—	—
Scroll attachment	A**	A**
General specifications		
Dimensions (D x W x H)		
- In use in in. (approx.)	14.6 x 15.8 x 33.1	14.6 x 15.8 x 33.1
- In use in mm (approx.)	370 x 400 x 840	370 x 400 x 840
- During transportation in in. (approx.)	—	—
- During transportation in mm (approx.)	—	—
Weight in lbs/kg (approx.)	25.4/11,5	27.6/12,5
GS German safety seal	•	•
Power	230 V/50-60 Hz	230 V/50-60 Hz

A** = Accessory

Ed. Liesegang oHG

Specialists in the Manufacture
of Projection and Presentation Equipment

Volmerswerther Straße 21

D-40221 Düsseldorf

Germany

Phone +49 211 3901-1

Fax +49 211 3901-227

info@liesegang.de

www.liesegang.de

Your Liesegang partner: