

HD-SDI / HDMI DIGITAL VIDEO CONVERTERS

CONNECT

DUAL-BATTERY
CONVERTERS

The world's
smallest 3G
Converters

Convert
uninterrupted
anywhere



H2S
HDMI → HD-SDI

Continuous Power*



S2H
HD-SDI → HDMI™



Test Pattern
& Audio Tone
Generator



Built-in
Pulldown
removal

Tiny, reliable, cascadable & future proof



Modular
Design

Stack up to
6 units or
rack mount



Connect Converters are the ultimate battery powered, in-the-field converter tool for any situation. With 3G/HD/SD-SDI and HDMI connectivity, internal and external battery options and Atomos' patent pending Continuous Power technology, you can convert anytime, anywhere.

Built for convenience, Connect Converters are lightweight and fit in your pocket. Powered by battery or AC, they provide 3:2 pulldown removal, test pattern and audio signal generation and even have a built-in flashlight for use in dark locations.

At Atomos we're all about innovation, so we've made Connect incredibly flexible. They're stackable and modular and you can cascade and power them from one source. They're even rack-mountable.*

CONNECT

DUAL-BATTERY CONVERTERS



Connect 3G/HD/SD-SDI & HDMI

Convert any HD/SD-SDI or HDMI signal, including 3G. Choose S2H for HD-SDI→HDMI and H2S for HDMI→HD-SDI

S2H HD-SDI→HDMI

all SDI types to HDMI; pulldown removal included

H2S HDMI→HD-SDI

HDMI to all SDI types pulldown removal included

Battery or AC power: 2 hours, 2 days or continuous supply

A portable device without a power supply is useless, but that will never happen with Connect converters.

With flexible battery and power options, you're covered for any eventuality – even an unexpected power loss. A built-in battery ensures that the show goes on if all else fails.

Multiple, stackable external batteries can be swapped without powering down, and any Connect battery configuration acts as a backup to AC power, at the same time as being charged from it.



Connect devices

In the field, studio, broadcast or editing:

No matter where you are, connecting Cameras, Lighting, Monitors, Decks, Capture Cards, Switchers, Routers & Satellite feeds is a breeze.

Connect to your field recorder

Attach to, and power, Atomos Ninja, Ninja-2 and Samurai.

In the field

- Very small and lightweight
- Battery powered (no AC needed)
- Full day's use from one battery
- Use with a mixture of devices - attach directly to battery plate

In the studio

- Fits anywhere
- AC or battery power
- Rack-mountable
- Run HDMI over SDI distances

Broadcast

- Integrate affordable HDMI equipment throughout your SDI infrastructure
- Connect HDMI devices to SDI switchers, routers and signal feeds

Editing & capture

- Affordable monitoring with SDI to HDMI conversion
- Easy conversion for cameras, decks, and capture cards

The Ultimate Video Tool

Not just the world's smallest 3G converter! A must-have tool for professional everyday use

Test Pattern Generator (TPG)

Convenient broadcast-quality test patterns for equipment verification on the fly anytime, anywhere!



3:2 Pulldown Removal (PDR)

Realtime Pulldown Removal. Extract 24P/30P from 60i & 25P from 50i or PSF equivalents



We've even included a flashlight

A built-in LED torch, so you can see what you're connecting to in the dark!



Dimensions	45.0mm (w) x 76.5mm (l) x 30.0mm (h)	Video Input	S2H: 3G/HD/SD-SDI x 1	H2S: HDMI x 1
Power Consumption	2W while converting	Video Out	S2H: 3G/HD/SD-SDI x 1 and HDMI x 1	H2S: 3G/HD/SD-SDI x 2
Batteries (NP Series, 7.4V - 16.8V)	• Internal up to 1 hour • 2600mAh - 10hrs (included) • 5200mAh - 20hrs (optional) • 7800mAh - 30hrs (optional) • AC Power Supply 100-240V (included) • DTap Adaptor (optional)	Audio (In/Out)	Embedded Audio 2ch, 24bit	
Continuous Power (Patent Pending)	Connect acts as a battery, feeding continuous power into your Ninja, Samurai, or another Connect.	Timecode	SDI: Sony, Canon, Panasonic, Arri, RED HDMI: Sony, Canon Timecode, Canon Start/Stop	
Built-in 3:2 and 2:2 Pulldown Removal	• 25PsF (50i)→25P • 30PsF (60i)→30P • 24p (3:2-60i)→24P	Supported Formats (In/Out)	1080p60, 1080p59.94, 1080p50, 1080i60, 1080i59.94, 1080i50, 1080p30, 1080p29.97, 1080p25, 1080p24, 1080p23.98, 1080psf30, 1080psf29.97, 1080psf25, 1080psf24, 1080psf23.98, 720p60, 720p59.94, 720p50, 486i59.94, 480i59.94, 576i50	
Test Pattern Generator	SMPTE 75%, Colour Bars 75 & 100%, SDI EQ/PLL Pathological, Audio Tone 1kHz @ -20dBfs			
USB Interface	Firmware Update Interface ONLY			



ATOMOS (HQ)
5 Eastbourne St.
Windsor VIC 3181
Australia

Enquiries: sales@atomos.com | Support: support@atomos.com | Telephone: +61 3-9999-5908 | www.atomos.com