

TRANSFORMER BALANCED ANALOGUE AUDIO DISTRIBUTION AMPLIFIER



DESCRIPTION

The AEQ DA-26 provides audio distribution from either one mono audio input to twelve mono outputs or from one stereo input to six stereo outputs. Independent gain control is provided for each individual output and all inputs and outputs are transformer balanced for greater system protection.

As transformers provide electrical isolation between the primary and secondary windings, this means that the signal connected to the input side is not physically or electrically connected to the output side. Therefore as there is no electrical connection between the input and output, transformers are used to prevent ground loops and other problems that occur when equipment is interconnected. This is a key feature of the DA-26.

APPLICATION

This 1U 19" rackmount unit is ideal for audio distribution applications where many audio outputs are required. For example in Press Centres, OB Vehicles, PA systems, programme distribution in radio and television stations, in fact anywhere signal distribution is required.

TECHNICAL FEATURES

Mono mode: 1 mono input, 12 stereo outputs
Stereo mode: 1 stereo input, 6 stereo outputs

All Inputs and outputs are transformer balanced

Audio Connectors: Hartmann male with solder-type mating connectors included
Max. input level: + 20 dB
Input impedance: 1.5 kOhms
Adjustable gain: +14 dB for each output
Output impedance: < 220 Ohms
Consumption: 8 VA
Universal auto-range PSU: 90-250V / 50-60 Hz
Power Input: Male 3-pin IEC
Size: 1U x 19" (482.6 x 44.5 x 130 mm)
Weight: 2.6 Kg.



AEQ USA

Phone: 866 817 9745 (Solo en US)
 Phone: + 1 (954) - 581 7999
 e-Mail: sales@aeqbroadcast.com

Fax: + 1 (954) - 581 7733
 url: www.aeqbroadcast.com

International Sales

Phone: +34 916 861 300
 e-Mail: aeqsales@aeq.es

Fax: +34 916 864 492
 url: www.aeq.es