

DA 124+

DUAL 1x4 VIDEO DISTR. AMPLIFIER

DA 124+ is a distributor for video signals with 2 separated inputs and 4 outputs each. May be employed as a normal distributor or as equalizer to compensate the long cable losses. May operate as 1x8 video distributor and is compatible with Y/C signals.

DA 124+ è un distributore per segnali video composti che può distribuire 2 segnali video separati ognuno verso 4 destinazioni.

Può essere impiegato come normale distributore o come equalizzatore per compensare le perdite di lunghe tratte di cavi.

Può funzionare come un distributore 1x8 ed è compatibile Y/C.



- One trimmer equalizer up to 100 mt of RG59 B/U cable
- Inputs linkable to obtain 1x8
- AC or DC input coupling
- Switch for 75 Ω termination

- Equalizzazione monotrimmer fino a 100 mt di cavo RG59 B/U
- Ingressi connettabili per avere 1x8
- Ingressi accoppiati in AC o DC
- Terminazione 75 Ω a switch



SPECIFICATIONS

Input type	:AC or DC switch select.
Input ret.loss	:35 dB at 5 MHz
Input level	:Max 1.5 Vpp on 75 Ω
Output gain	:0 dB
Output ret.loss	:36 dB at 5 MHz
Frequency response	:0.1 dB at 10 MHz -3 dB at 60 MHz
Delay	:15 ns
Differential gain	:0.2%
Differential phase	:0.8°
Hum & noise	:-90 dB unweighted
Crosstalk (two sections)	:60 dB at 5 MHz

Main input	
(with AC adapter ADM 001)	:230 Vac 50 Hz
Power consumption	:5 VA
Size (WxDxH)	:200 x 100 x 44 mm
Weight	:0.5 Kg
Operating temp. range	:0 + 45°C
Safety	:according to EN 60065
EMC	:according to EN 55103-1 and EN 55103-2

ELPRO Video Labs s.r.l.

Strada della Pronda, 45/B
10142 Torino-ITALY
Tel.+39 0117701583 – Fax +39 011703751

E-mail: info@elprovideolabs.com
[http:// www.elprovideolabs.com](http://www.elprovideolabs.com)

