

DVR-LCD 4/8 are units that include, in the same product, a digital video recorder with 120 Gbyte HD, a 15" LCD monitor with SXGA resolution, a CD writer to obtain the backup of the images recorded on HD and the PTZ camera control in RS485.

The units have 4/8 video looping inputs and a twin video output. On the outputs and on the LCD monitor it's possible to display a single input or 4/8 inputs in multiview mode.

Through the software provided it's possible to create, by TCP/IP streaming video, the remote displaying of the images shown on the local LCD monitor.

DVR-LCD4/8, thank their compact characteristics, are very useful in security applications and for monitoring in room control.



- 15" LCD display
- Multiview function in real time: 4 or 8 channels
- The best picture quality in Playback(JPEG-2000)
- 4/8 channel @ 240(200)ips recording capability
- Triplex (Playback/Recording/Ethernet)
- Remote monitoring and download through LAN/Internet
- Easy PTZ camera control by pre-assigned buttons
- Password Protection
- IR Remote Controller
- RS232 control
- Wall montable

DVR-LCD 4/8 sono unità che racchiudono, nello stesso prodotto, un digital video recorder con HD da 120 GByte, un monitor LCD da 15" con risoluzione SXGA, un masterizzatore CD per realizzare il backup delle immagini registrate su HD ed i controlli camera PTZ in RS485. Le unità hanno 4/8 canali di ingresso video a loop e una doppia uscita video. Sulle uscite e sul display LCD è possibile visualizzare un singolo canale oppure i 4/8 canali contemporaneamente in modalità multiview.

Tramite il software fornito col prodotto è possibile remotizzare in streaming video, via TCP/IP, le immagini visualizzate su LCD.

DVR-LCD4/8, grazie alle caratteristiche di compattezza, sono molto utili in applicazioni di sicurezza e nel monitoraggio in sale di controllo.



- 15" LCD display
- Funzione Multiview in tempo reale: 4 o 8 canali
- Migliore qualità immagine in Playback (JPEG-2000)
- 4/8 canali @ 240(200)ips capacità di registrazione
- Triplex (Playback/Recording/Ethernet)
- Monitoring e download remoto tramite LAN/Internet
- Facile controllo camera PTZ con pulsanti preassegnati
- Password di protezione
- Telecomando IR
- Controllo RS232
- Possibilità di montaggio a muro

SPECIFICATIONS

Multiplex function	:Triplex (Playback/Recording/Ethernet)
Storage Capacity	:Internal HDD 120 GByte :CD-RW For Backup
Video Inputs	:Composite 4 Ch or 8 Ch
Video Outputs	:Loop out 4 Ch or 8 Ch :Composite 2 Ch
Compression	:JPEG-2000
Compression Rate	:Basic, Normal, Enhanced, Fine, Super (Image size fixed)
Display Speed	:Real Time display
Recording Mode	:Time, Motion, schedule, Alarm
Search	:Event Search, Date/Time Search
Rec. Speed (NTSC/PAL)	:Full (60/50), Dual (120/100)
Rec. Resolution (NTSC/PAL)	:720x240/720x288
Display	:15" LCD with XGA resolution
Live Division Screen	:1 / 4 Split
Additional func	:Digital Zoom, Freeze function available in Live mode, PIP
Switching Interval	:1~99 sec selectable

Alarm Inputs	:4 Alarms (NO/NC selectable by menu)
Alarm Outputs	:1 (NO/NC)
Post Alarm	:Duration alarm output : 1 to 59 sec
Motion Detection	:Area division : 16 x12 :Detection Division : 32 x 24
Network Backup	:Ethernet (TCP/IP), Remote viewer SW :VCR, CD-RW back-up, Download via IP Network
PTZ Control	:RS-485, Key Control (Key assigned for each PTZ command)
Serial I/F	:RS-485 for PTZ camera control RS-232 for PC control
Power Requirements	:DC 12 V 6.6 A Adaptor
Size (WxDxH)	:356,4 x 68,5 x 330
Weight:	:8,3 Kg
Operating temp.range	:0+45°
Safety	:according to EN60065
EMC	:according to EN55103-1 and EN55103-2

ELPRO Video Labs s.r.l.

Strada della Pronda, 45/B
10142 Torino-ITALY
Tel.+39 0117701583 – Fax +39 011703751

E-mail: info@elprovideolabs.com
[http:// www.elprovideolabs.com](http://www.elprovideolabs.com)

