

INBOX/8 PLUS HIGH RESOLUTION GRAPHIC DISTR.

INBOX/8 PLUS is a computer and workstation graphic signals distributor with one input and eight outputs.

Its excellent features with a careful design make this unit very useful for heavy and continuous use.

Show rooms, airports, museum, stores and hotels are the main fields of application.

ID bit presetting on HDD input connector is provided as well to activate the graphic card of some notebook.

L'unità INBOX/8 PLUS è un distributore di segnali grafici di computer e workstation con un ingresso e otto uscite.

Le ottime caratteristiche tecniche unite ad un generoso dimensionamento dei componenti rendono questa unità particolarmente utile per impieghi gravosi e continuativi.

Show rooms, aeroporti, musei, grandi magazzini ed hotels sono i principali campi di applicazione.

E' inoltre provvista della predisposizione ID bit sul connettore HDD di ingresso che consente di attivare la grafica di alcuni notebook.



- Eight buffered outputs
- Compensation up to 50 mt. SVGA cable
- All formats compatible
- Linkable in cascade
- 400 MHz bandwidth
- Self powered

- Otto uscite amplificate
- Compensazione fino a 50 mt. cavo SVGA
- Compatibile con qualunque formato
- Collegabile in cascata
- Banda di 400 MHz
- Alimentatore all'interno



SPECIFICATIONS

RGB Signals	: analog, 700mVpp on 75 Ω nom.
Coupling	: DC
Synchronism	: Hs and Vs TTL pos/neg
Input connector	: n°1 HDD15p.f.
Out connectors	: n°8 HDD15p.f.
Bandwidth	: 400 MHz
Driving capability	: >50 mt. SVGA cable (Boost 1÷8 ON)

Main input	: 230 Vac 50 Hz (115 Vac 60 Hz on request)
Power consumption	: 6 VA
Size (WxDxH)	: 483 x 140 x 44 mm
Weight	: 2 Kg
Operating temp. range	: 0 ÷ 45°C
Safety	: according to EN 60065
EMC	: according to EN 55103-1 and EN 55103-2

ELPRO Video Labs s.r.l.

Strada della Pronda, 45/B
10142 Torino-ITALY
Tel. +39 0117701583 – Fax +39 011703751

E-mail: info@elprovideolabs.com
<http://www.elprovideolabs.com>

