

JVC[®]

The Perfect Experience / —
/

New Product News

TENTATIVE

LM-170

17-inch TFT-LCD 5:4 1280 x 1024 (SXGA)

LM-150

15-inch TFT-LCD 4:3 1024 x 768 (XGA)



SXGA or XGA Resolution

High Reliability

- Full Metal Cabinet
- Corner Protector
- Tough Control Keys

Professional Features

- Convenient Scan Mode
- Easy Control Front Keys
- Wired Remote
- BNC Connector
- Rack Mount Capability
- CTI On/Off
- Security Category Regulations

Easy Installation

- Slimmer Bezel and Square Design
- VESA100 Mounting Holes
- Screw Holes for Installation
- Flush Wall Mounting Capability
- Built-In Power Supply

Specifications

		LM-170	LM-150
Type		LCD display monitor	LCD display monitor
Color system	NTSC and PAL	NTSC and PAL	NTSC and PAL
LCD panel	Size	17" TFT-LCD 5:4	15" TFT-LCD 4:3
	Type	TFT	TFT
	Pixels	1280 x 1024	1024 x 768
	Luminance	400 cd/m ²	400 cd/m ²
	Viewing angle (Typical)	Vertical: 130° Horizontal: 140°	Vertical: 120° Horizontal: 140°
	Power requirements	AC 120V/220-240V, 50Hz/60Hz	AC 120V/220-240V, 50Hz/60Hz
Input terminals	Component	D-sub 15-pin	D-sub 15pin
	Video	BNC x 2, bridged	BNC x 2, bridged
	PC	D-sub 15-pin DVI-D	D-sub 15-pin DVI-D
Internal signal	Video	NTSC, PAL, B/W, manual select	NTSC, PAL, B/W, manual select
	PC	fh: 15k/31kHz-80kHz fv: 56Hz-75Hz	fh: 15k/31kHz-60kHz fv: 56Hz-75Hz
	Supported range of resolutions	VGA, SVGA, XGA and SXGA	VGA, SVGA, and XGA
Audio terminals	2-line mono, 2-line phone, Front mono speaker	—	
Remote control	Make Control or Trigger Pulse/OSD selectable	Make Control or Trigger Pulse/OSD selectable	
Cabinet material	Slim bezel and full metal/cabinet	Slim bezel and full metal/cabinet	
Mounting hole	VESA 100 mm pitch	VESA 100 mm pitch	
Dimensions (W x H x D)	374 x 334 x 70.5 mm (without stand)	342 x 291 x 70.5 mm (without stand)	
Provided accessories	Detachable power cable and stand unit (with tilt and height)	Detachable power cable and stand unit (with tilt and height)	

Controls

LM-170 Control Panel



KEY FUNCTIONS


SCAN SIZE	100% or OVER SCAN selectable. User adjustable.
NO SYNC FUNCTION	OFF, SLEEP or GRAY BACK selectable
CONTROL LOCK	Front Key Lock
STATUS DISPLAY	Auto status of on-screen display ON/OFF selectable.
CTI	Color transient improver On/Off selectable. TV-like vivid picture at function ON.
ASPECT	4:3, 16:9 selectable for squeezed pictures. Controllable from MENU or Remote.

Supplied Tilt and Height Stand



Input Terminals

LM-170 Rear Panel



INPUT	FORMAT or SYSTEM
VIDEO	NTSC / PAL selectable
RGB ANALOG	VGA ~ SXGA 60 / 15kHz RGB signal
DVI-D	VGA ~ SXGA 60 (tentative)
AUDIO	RCA : LINE IN mono Phono : For PC
REMOTE (RJ45)	Make Contact or TRIGGER Pulse system selectable LAN Wire RJ45 used. It reduces total system cost.

Optional Accessories

- RK-C157L1GA Rack Mount Adapter
- TS-CV10WG Wall Mount Bracket

*E. & O.E. Design and specifications subject to change without notice All TV screen pictures are simulated
All brand or product names may be trademarks and/or registered trademarks of their respective owners.
Any rights not expressly granted herein are reserved.*

Copyright © 2006, Victor Company of Japan, Limited (JVC). All Rights Reserved.

JVC®

DISTRIBUTED BY