



# KRAMER

## PT-572+

HDMI HDCP 2.2 Compact Receiver over PoC | HDMI | HDCP Compliant | DGKat | Kramer Core  
Long-Reach DGKat

---



The PT-572+ is a DGKat™ twisted pair receiver for HDMI signals. The PT-571 converts an HDMI signal to a single twisted pair signal and the PT-572+ converts the twisted pair signal back to an HDMI signal

## FEATURES

---

**Max. Data Rate** - 4.95Gbps (1.65Gbps per graphic channel)

**HDTV Compatible**

**HDCP Compliant**

**DGKat™ Signal Integration** - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables. We strongly recommend using Kramer DGKat™ cables designed specifically for optimum performance

**HDMI Support**

**3D Pass-Through**

**System Range** - Up to 90m (295ft) at 1080i, or up to 30m (98ft) at 1080p on shielded BC-DGKat524 cable. Up to 90m (295ft) at 1080i, or up to 70m (230ft) at 1080p on shielded BC-DGKat623 cable. Up to 100m (330ft) at 1080i or up to 90m (295ft) at 1080p on shielded BC-DGKat7a23 cable

**Cable** - Requires Shielded Twisted Pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat7a23 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground

**EDID PassThru** - Passes EDID signals between the source and display

**Status LED** - Lights red when receiving power only, orange when output and power are attached, and yellow when both an active input and output are attached

**Power Connect™ System** - A single connection to the transmitter or the receiver powers the system when the devices are within 270ft (90m) of each other

**Ultra-Compact Pico TOOLS™** - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUTS:	1 RJ-45 connector
OUTPUTS:	1 HDMI connector
BANDWIDTH:	4.95Gbps (1.65Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
POWER CONSUMPTION:	12V DC, 250mA
INCLUDED ACCESSORIES:	Power supply
OPTIONS:	RK-4PT 19" rack adapter
PRODUCT DIMENSION:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx
SHIPPING DIMENSION:	17.40cm x 12.00cm x 8.60cm (6.85" x 4.72" x 3.39" ) W, D, H
SHIPPING WEIGHT:	0.4kg (0.8lbs) approx

