

## More Brightness, More Excitement



The PT-AH1000E lets friends and family enjoy Full-HD large screen entertainment from movies, sports to video games.

Whether this projector is used for a house party filled with friends or for family movie night, the PT-AH1000E will provide everybody with vivid, clear and stunning video content.

### Large-Screen Entertainment for the Group

- 2,800 lumens of high brightness from newly developed 280W Red-Rich Lamp.
- Light Harmonizer 3 automatically adjusts the white balance, gamma curve and enhancer of the image to match the surrounding conditions with the built-in ambient light and colour sensors.
- Seven picture modes for various viewing situations, including modes that are ideal for sports, games and movies. (Dynamic, Game, Sports, Rec. 709, Cinema 1, Vivid Cinema and Normal).
- Motion Effect adds smoothness and sharpness to fast-moving scenes.

### Superb Picture Quality

- Outstanding 50,000:1 contrast ratio made possible via new high-precision optical system technology.
- Dynamic Iris Pro adds beauty to both dark and bright scenes.
- Pure Colour Filter Pro for rich, vibrant colours.
- Detail Clarity Processor 3 for fine detail reproduction.
- 16-Bit digital processing produces smooth gradation.
- Split Adjust mode for easy picture adjustment.
- Waveform monitor for precise calibration makes sure full dynamic range is in use.

### Installation Flexibility and Ease of Use

- 2x optical zoom/focus.
- V/H lens shift (vertical  $\pm 68\%$ , horizontal  $\pm 26\%$ ).
- VIERA Link for easy control of multiple Panasonic devices.
- Eco Management function for smart power consumption control.
- Two HDMI™ inputs (supporting x.v.Colour™ and Deep Colour).
- Two programmable 12-volt trigger terminals.
- User-friendly ergonomic remote control featuring a Function button and Eco button.

### Other Features

- Advanced Gamma Adjustment function allows precise calibration according to the signal source and environment.
- Cinema Colour Management allows individual colour correction.
- Progressive cinema scan (3/2 pulldown).
- 24p compatibility.
- Scene-adaptive MPEG noise reduction.
- Built-in test pattern.
- Screen memory.
- Up to sixteen sets of adjustment settings can be stored in memory with custom names that make them easy to remember.
- Easy lamp replacement from the top.
- A 3,000-hour\*1 lamp replacement cycle
- Easy filter replacement from the side.
- Quiet operation: 29 dB (lamp mode: eco).
- Made in Japan.

### Ecology-Conscious Design

- No halogenated flame retardants are used in the cabinet.
- Non-coated cabinet for easy recycling.
- Lead-free glass for the lens.
- Standby power consumption of only 0.08 W (standby mode: eco).
- "ECO" button on the remote control.
- An off-timer that reduces wasteful power consumption.
- RoHS compliant.

\*1 Lamp mode: Eco

## Specifications (Tentative)

<b>Power supply</b>	100–240 V AC, 50/60 Hz	<b>Terminals</b>	
<b>Power consumption</b>	350 W (0.08 W in standby mode with fan stopped.)	<b>HDMI IN</b>	HDMI connector × 2, HDMI™ (Deep Colour, x.v.Colour™*7, CEC*8), HDCP compliant, supports HDAVI Control Version 5
<b>LCD*1 panel</b>		<b>COMPUTER (RGB) IN</b>	D-sub HD 15-pin (female) × 1 (RGB/YPbPr × 1)
<b>Panel size</b>	18.7 mm (0.74 in) diagonal (16:9 aspect ratio)	<b>COMPONENT IN</b>	RCA pin × 3 (YPbPr/YCbCr)
<b>Display method</b>	Transparent LCD panel (× 3, R/G/B)	<b>TRIGGER IN/OUT</b>	M3 × 2, 12 V, max. 100 mA (input/output selectable using on-screen menu)
<b>Drive method</b>	Active matrix	<b>VIDEO IN</b>	RCA pin × 1
<b>Pixels</b>	2,073,600 (1,920 × 1,080) × 3, total of 6,220,800 pixels	<b>S-VIDEO IN</b>	Mini DIN 4-pin × 1
<b>Lamp*2</b>	280 W UHM lamp	<b>SERIAL IN</b>	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)
<b>Lens</b>	Manual zoom (1.33–2.69:1), manual focus, F 2.0–3.4, f 21.5–43.0 mm	<b>Power cord length</b>	3.0 m (9 ft 10 in)
<b>Projection size (diagonal)</b>	1.02–7.62 m (40–300 inches)	<b>Cabinet materials</b>	Moulded plastic (PC+ABS)
<b>Colours</b>	Full colour (1,073,741,824 colours)	<b>Dimensions (W × H × D)</b>	470 mm × 137 mm × 380 mm*9 [18-1/2" × 5-13/32" × 14-31/32"]*9
<b>Brightness*3</b>	2,800 lumens*4	<b>Weight*10</b>	Approx. 8.6 kg (19.0 lbs)
<b>Centre-to-corner uniformity ratio*3</b>	85%	<b>Operation noise*3</b>	29 dB (lamp mode: eco)
<b>Contrast ratio*3</b>	50,000:1*5 [full on/full off]	<b>Operating temperature</b>	0°–40°C (32°–104°F)
<b>Resolution</b>	1,920 × 1,080 pixels	<b>Operating humidity</b>	20%–80% (no condensation)
<b>Scanning frequency</b>		<b>Remote control unit</b>	
<b>RGB</b>	fh: 15 kHz–74 kHz, fv: 24 Hz–85 Hz, dot clock: 154 MHz or lower	<b>Power supply</b>	3 V DC (R6/AA type battery × 2)
<b>YPbPr (YCbCr)</b>	525i (480i), 625i (576i), 525p (480p), 625p (576p), 750 (720)/60p, 750 (720)/50p, 1125 (1080)/60i, 1125 (1080)/50i, 1125 (1080)/24p, 1125 (1080)/60p, 1125 (1080)/50p	<b>Operation range*11</b>	Approx. 7 m (23 ft) when operated from directly in front of the signal receptor
<b>Video/S-Video</b>	fh: 15.75 kHz, fv: 60 Hz [NTSC/NTSC4.43/PAL-M/PAL60] fh: 15.63 kHz, fv: 50 Hz [PAL/PAL-N/SECAM]	<b>Dimensions (W × H × D)</b>	48 × 138 × 28.3 mm [1-7/8" × 5-7/16" × 1-1/8"]
<b>Optical axis shift*6</b>	Vertical: ±68%, horizontal: ±26%	<b>Weight</b>	Approx. 125 g (4.4 oz) (including batteries)
<b>Keystone correction range</b>	Vertical: approx. ±30°	<b>Supplied accessories</b>	Power cord (× 1) Wireless remote control unit (× 1) Batteries for remote control (R6/AA type × 2) Lens cover (× 1)
<b>Installation</b>	Ceiling/desk, front/rear (menu selection)	<b>Optional accessories</b>	
<b>On-screen menu languages</b>	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Swedish, Danish, Norwegian, Polish, Czech, Hungarian, Portuguese, Thai, Japanese	Replacement lamp unit	ET-LAA110
		Ceiling mount bracket for high ceilings	ET-PKA110H
		Ceiling mount bracket for low ceilings	ET-PKA110S

- \*1 The projector uses a type of liquid crystal panel that typically consists of millions of pixels. This panel is built with very high-precision technology to provide the finest possible image. Occasionally, a few pixels may remain turned on (bright) or turned off (dark). Please note that this is an intrinsic characteristic of the manufacturing technology that affects all products using LCD technology.
- \*2 The projector uses a high-voltage mercury lamp that contains high internal pressure. This lamp may break, emitting a large sound, or fail to illuminate, due to impact or extended use. The length of time that it takes for the lamp to break or fail to illuminate varies greatly depending on individual lamp characteristics and usage conditions.
- \*3 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards.

- \*4 In dynamic mode, with dynamic iris on.
- \*5 In cinema 1 mode, with dynamic iris on.
- \*6 Shift range is limited during simultaneous horizontal and vertical shifting.
- \*7 Effective in Rec. 709 picture mode.
- \*8 CEC is an abbreviation for Consumer Electronics Control. Operation may not be possible with some connected equipment or settings.
- \*9 Lens and legs not included.
- \*10 Average value. May differ depending on models.
- \*11 Operation range differs depending on environments.

# Panasonic®

For more information about Panasonic projectors  
 >>> <http://panasonic.net/avc/projector>  
 Panasonic projectors facebook page  
 >>> <http://www.facebook.com/panasonicprojector>



Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. This product may be subject to export control regulations. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. All other trademarks are the property of their respective trademark owners.  
 © 2011 Panasonic Corporation. All rights reserved.

All information included here is valid as of August 2011.

PT-AH1000PRE1 Printed in Japan.