

For more information visit
www.vinten.com

Sales Offices

CHINA
Room 1806, Hua Bin Building
No. 8 Yong An Dong Li
Jian Guo Men Wai Ave
Chao Yang District
Beijing, P.R.China 100022

t +86 10 8528 8748
f +86 10 8528 8749

FRANCE
171, Avenue des Grésillons
92635 GENNEVILLIERS Cedex
France

t +33 820 821 336
f +33 825 826 181

GERMANY
Gebäude 16
Planiger Straße 34
55543 Bad Kreuznach
Germany

t +49 671 / 483 43 30
f +49 671 / 483 43 50

UK
William Vinten Building
Western Way
Bury St Edmunds
Suffolk IP33 3TB
UK

JAPAN
P.A. Bldg. 5F
3-12-6 Aobadai
Meguro-ku Tokyo 153-0042
Japan

t +81 3 5456 4155
f +81 3 5456 4156

SINGAPORE
6 New Industrial Road
#02-02 Hoe Huat Industrial
Building
Singapore 536199

t +65 6297 5776
f +65 6297 5778

USA
709 Executive Blvd
Valley Cottage
NY 10989
USA

t +1 845 268 0100
f +1 845 268 0113
Toll Free Sales: 1 888 2 Vinten

Protouch Systems Protouch lightweight camera support



VintenProtouch
Lightweight Camera Support System



Changes in Product Specification

Vinten reserve the right to alter specifications or change materials where absolutely necessary. All sizes shown throughout this brochure are approximate and colours shown are as accurate as modern reproduction methods will allow. No liability can be accepted for any variation.

© 2007 The Vitec Group plc
© VINTEN, VISION, VECTOR, QUICKFIX & QUICKFIT are registered trademarks of The Vitec Group plc.

QUALITY SYSTEMS APPROVED TO ISO 9001:2000
Certificate No. Q09508

V1/08/07

Vinten

simply perfection

ProtouchSystems | Protouch lightweight camera support

Vinten

simply perfection

www.vinten.com

Vinten Protouch Systems: Introducing the Pozi-Loc Tripod

Unrivalled torsional rigidity transferred from the award winning Vision Range

Picture quality relies as much upon the rigidity of the camera support as it does on the smoothness of the pan & tilt head and accuracy of the counterbalance. Protouch is unique because it includes the Pozi-Loc tripod synonymous with the Vision Range.

Vinten Pozi-Loc was designed to optimise rigidity without compromising operational essentials such as weight, reliability, maintenance and speed of set-up. This special edition Protouch black aluminium Pozi-Loc tripod completes the picture, making Protouch the best value high performance system on the market.

The importance of Vinten design.



The **Protouch** range has been introduced to appeal to those working in event videography and the corporate sector, enabling videographers to maintain a professional look and feel to their work whilst managing a tight budget.

The **Pro-10** and the **NEW Pro-6^{HDV}** offer the perfect solution for supporting the ever-increasing range of professional DV camcorders from 2kg to 10kg.

The Protouch heads feature continuously variable fluid drag and the capacity to handle the smallest DV camcorder to today's generation of multi-purpose ENG format cameras. This ensures that these lightweight heads provide smooth movement and complete camera control for any application. Designed to be simple to use the Pro-6^{HDV} and Pro-10 incorporate easy to adjust drag knobs and an illuminated levelling bubble for quick and convenient set up in low light situations.

The Protouch range offers a truly professional alternative, backed by the Vinten brand.



Pro-6^{HDV}

For the new generation of camcorders up to 6kg



NEW

Sideload system allows for rapid camera attachment, adjustment and removal.



3 levels of counterbalance plus zero position for extremely lightweight camcorders and easy to adjust pan and tilt drag.



Illuminated levelling bubble for quick and convenient set up in low light situations.



Pro-6^{HDV} is available as an off the shelf head or incorporated into two lightweight systems with the Vinten Pozi-Loc tripod (see page 2), a branded black fabric system case (see page 3) and either the standard floor spreader or a new lightweight mid-level spreader that offers a much wider range of stable footprints for any location or terrain.

Continuously variable fluid pan and tilt drag and stepped counterbalance up to 6kg (13.2lbs) ensures that the Pro-6^{HDV} head provides smooth movement and complete camera control.

- Pro-6^{HDV}F System with floor spreader
- Pro-6^{HDV}M System with mid-level spreader
- V4018-0001 Pro-6^{HDV} pan & tilt head

Pro-10

For larger cameras up to 10kg (22lb)



Illuminated levelling bubble for quick and convenient set up in low light situations.



The **Pro-10** camera support system is the perfect combination for the latest professional digital and ENG cameras. Providing exceptional value for money the system comprises of the Pro-10 pan & tilt head, Pozi-Loc two-stage tripod (see page 2), a floor spreader and soft case.

The Pro-10 head provides smooth control and movement through 360° of pan and +90° to -60° of tilt with continuously variable fluid drag.

- Pro-10DC System with floor spreader
- 3809-3 Pro-10 pan & tilt head

Dolly

The **Protouch PD114 multi-purpose dolly** is an ideal optional accessory for any Protouch system. The lightweight and compact folding dolly is supplied with individual wheel locks and removable cable guards, making it ideal for studio and outside applications.

U005-103 Dolly



Spreaders



A **spreader** is essential, it maximises stability, allowing the camera operator to utilise the full performance of the pan and tilt head.

The Protouch floor spreader offers the most stability and a generous amount of flexibility, but the terrain may be too rough and prevent its use. Therefore, a mid-level spreader can be the safest option to ensure stability and camera control in any situation.



The **new** lightweight mid-level spreader, suitable for both systems, allows individual telescopic adjustment of each leg and provides a wide range of stable footprints. The overall footprint is determined by a two position central selector allowing for an extremely small footprint for tight areas and a large footprint where conditions allow.

3818-3 Ground spreader
V4032-0001 Mid-level spreader (with 3 rubber feet)

Vinten Service & Support

When you buy **Vinten** a global team of customer service professionals ensures that technical advice, training and service backup is always available. You can also register your product online to receive a **FREE 2 year warranty**.

Technical Specification		
Pro-6 ^{HDV} Pan & Tilt head		
Type No:	V4018-0001	
Capacity:	Maximum 6kg (13.2lb) @ 55mm (2.2") CofG	
Weight:	2.2kg (4.8lb)	
Tilt Range:	+90° -60°	
Pan Range:	360°	
Counterbalance:	Selectable 3 steps plus zero	
Pan & Tilt Drag:	Infinitely adjustable	
Camera Fixing:	Quick attachment and release Sideload system, utilising a standard slide plate complete with 3/8" and 1/4" camera screws with locating pin	
Ball Base:	75mm	
Levelling Bubble:	Illuminated with low battery indicator	
Pan Bar:	Single fixed length	
Pro-6 ^{HDV} M System		
Type No:	Pro-6 ^{HDV} M	
Weight:	7.25kg (16.0lb)	
Consisting:	Pro-6 ^{HDV} head, tripod, mid-level spreader, soft case and multi-lingual operator guide	
Pro-6 ^{HDV} F System		
Type No:	Pro-6 ^{HDV} F	
Weight:	7.35kg (16.2lb)	
Consisting:	Pro-6 ^{HDV} head, tripod, floor spreader, soft case and multi-lingual operator guide	
Pro-10 Pan & Tilt Head		
Type No:	3809-3	
Capacity:	10 kg / 22 lbs	
Weight:	2.4 kg / 5.2 lbs	
Tilt Range:	+90° -60°	
Pan Range:	360°	
Counterbalance:	Fixed for a 7.5kg /16.5 lb camera weight	
Camera Fixing:	Sliding quick release plate (interchangeable with Vision 3 & 6) with 3/8" and 1/4" screws with locating pin	
Ball Base:	75 mm	
Levelling Bubble:	Illuminated	
Pan Bar:	Single fixed length	
Pro-10DC System		
Type No:	Pro-10DC	
Weight:	8.2 kg / 18.1 lbs	
Consisting:	Pro-10 head, tripod, spreader, soft case and multi-lingual operator guide	
PD114 Dolly		
Type No:	U005-103	
Capacity:	40 kg / 88.2 lbs	
Weight:	5.2 kg / 11.5 lbs	
Base Diameter:	112 cm / 44.1"	
Wheel Diameter:	12.5 cm / 5"	
Pozi-Loc Tripod		
Weight:	3.2 kg / 7lbs	
Min Height:	41.6cm / 16.4"	
Max Height:	156.2 cm / 61.5"	
Transport Length:	71 cm / 28"	
Head Fixing:	75 mm bowl	
Spares and Accessories		
12v MN21	Battery (Pro-10)	
3v CR1220	Battery (Pro-6 ^{HDV})	
3330-35	Bowl Clamp	
3808-900SP	Camera plate (Pro-6 ^{HDV}) incl. 3/8" & 1/4" screws and location pin	
3809-900SP	Camera plate (Pro-10) incl. 3/8" & 1/4" screws and location pin	
3330-33	Extended length camera plate incl. 2 x 3/8" screws	
3219-104	Fixed length pan bar	
U005-190	Pro-10 soft system case	
U005-190B	Pro-6 ^{HDV} soft system case	
3330-243	75mm ball to 100mm tripod bowl adaptor	
3425-3P	Carrying strap incl. fixing kit and instructions	