

S-1073H

7" Full HD 4K-HDMI LCD Monitor

■ Features

- ◆ 7" non-glaring LCD, 1920 × 1200 resolution
- ◆ 2K/3G/HD/SD-SDI input & loop output
- ◆ HDMI 2.0 (4K60p) input & loop output
- ◆ Up to 16-ch embedded audio meters with alert
- ◆ Select any 2 audio channels to output
- ◆ 9 steps quick zoom-in and mapping
- ◆ Peaking focus assist with precision adjustment
- ◆ Build-in multi-camera logs to Rec.709 conversion
- ◆ User 3DLUT cube file import by USB
- ◆ On-screen soft TALLY display and GPI control
- ◆ Zebra stripes, False color, R/G/B/Mono
- ◆ H/V delay, AFD, Timecode display
- ◆ Marker 4:3, 13:9, 14:9, 15:9, 1.85:1, 2.35:1
- ◆ 6.5-36V wide input voltage
- ◆ V-mount or Gold mount or various DV plates option
- ◆ USB firmware upgrade



■ Package includes

Standard package includes		Luxury Package includes additional		

■ Specification

LCD Performance		
Size	7 inches	
Display area	151.2 × 94.5 mm	
Resolution	1920 × 1200	
Color	8 bit	
Aspect ratio	16:9 / 4:3	
Brightness	400 cd/m ²	
Contrast	1000:1	
Viewing Angle	H/V:160°/160°	
Input/output		
Input	HDMI × 1	HDMI input
	BNC × 2	3G/HD/SD-SDI input
	USB × 1	
Output	HDMI × 1	HDMI loop output
	BNC × 1	3G/HD/SD-SDI loop output
	3.5mm × 1	SDI/HDMI analog audio output
Video Format		
SDI	SMPTE-2048-2	2048 × 1080p (23.98 / 24 / 25 / 29.97 / 30 / 50 / 59.94 / 60)
		2048 × 1080i (50 / 59.94 / 60)
	SMPTE-425M-A/B	1080p (60 / 59.94 / 50)
		1080i (60 / 59.94 / 50)
	SMPTE-274M	1080p (30 / 29.97 / 25 / 24 / 23.98)
		1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-RP211	720p (60 / 59.94 / 50)
SMPTE-296M	480i (59.94)	
ITU-R BT.656	576i (50)	
HDMI	480i / 576i / 480p / 576p	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
	1080psf (30 / 29.97 / 25 / 24 / 23.98)	
	4096X2160 (60 / 50 / 30 / 25 / 24)	
	3840X2160 (60 / 50 / 30 / 25 / 24)	
General		
Input voltage	DC / Battery: 6.5V ~ 36V	
Power consumption	9 ~ 13W	
Working temperature	-10°C ~ +50°C	
Working humidity	10% ~ 90%	
Storage temperature	-15°C ~ +60°C	
Storage humidity	10% ~ 90%	
Dimensions	187 × 137 × 41mm	
Net weight (main body)	500 g	

Distributed by:

SWIT Electronics Co., Ltd.

Website: www.swit.cc Tel: +86 25 85805753
 Email: contact@swit.cc Fax: +86 25 85805296