



9-inch Full HD 3GSDI & HDMI LCD Monitor

S-1092H



Introduction:

The S-1092H monitor adopts a 9-inch IPS LCD panel, with 1920x1200 high resolution and H/V 170° viewing angle.

The monitor supports 3G-SDI, HDMI and CVBS input, with embedded audio meters display, peaking focus assist, Pic-in-Pic display, various scale markers and GPI control interface for professional HD video production monitoring.

S-1092H can be powered via 4-pin XLR 6.5-24V DC input or V-mount / Gold mount / Snap-on DV battery mounts.

Features:

- ◆ 9-inch IPS LCD Panel with LED backlight
- ◆ 1920x1200 resolution, 800:1 contrast
- ◆ H 170°/V 170° viewing angle
- ◆ 3G/HD/SD-SDI, HDMI, CVBS input
- ◆ Embedded audio meters display
- ◆ SDI/HDMI and CVBS PIP display
- ◆ Peaking focus assist (red/blue switch)
- ◆ SDI timecode display
- ◆ Red/Green/Blue only, Zebra stripes
- ◆ Underscan / Overscan switch
- ◆ Pixel-to-Pixel and SD 2x zoom-in display
- ◆ Scale marker 4:3, 13~15:9, 1.85:1, 2.35:1
- ◆ Front and rear 3-color TALLY light
- ◆ User definable GPI control
- ◆ Customer editable video TITLE
- ◆ V-mount / Gold mount / DV mount optional

Simple Package includes:



Sun hood



Articulating arm
1/4" or cold shoe



4-pin XLR
power adaptor



V-mount / Gold mount /
DV mount optional

Luxury Package has additional:



Carrying case



D-tap to 4-pin XLR
DC cable



U shape desktop stand

Specifications:

LCD Performance

Size	9 inches
Resolution	1920x1200
Display area	192x120mm
Aspect ratio	16:9/4:3
Color system	NTSC/PAL
Brightness	450cd/m2
Contrast	800:1
Color	16.77 million colors
Viewing angle	H/V:170/170

Input and Output

Input	2 BNC	(2) 3G/HD/SD-SDI in
	1 BNC	(1) Composite in
	1 HDMI	(1) HDMI in
	1 3.5mm	(1) Analog audio in
Output	1 BNC	(1) 3G/H D/SD-SDI loop through out
	1 HDMI	(1) HDMI loop through out
	1 3.5mm	(1) SDI/HDMI/Analog audio out

Video Format

SDI	SMPT-425M	1080p (60 / 59.94 / 50)
	SMPT-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPT-296M	720p (60 / 59.94 / 50)
	SMPT-125M	480i (59.94)
ITU-R BT.656	576i (50)	
HDMI	480i / 576i / 480P / 576P	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
		1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)
Composite	PAL/NTSC	

General

Working voltage	DC/ Battery 6.5V-24V
Power consumption	≤ 18W
Working temperature	0°C ~ +40°C
Working humidity	10% ~ 90%
Storage temperature	-15°C ~ +60°C
Storage humidity	10% ~ 90%
Dimensions	241x178x52mm
Net weight	1.1kg

SWIT Electronics Co., Ltd.

Website: www.swit.cc

Email: contact@swit.cc

Tel: +86 25 85805753

Fax: +86 25 85805296