

S-4913T/R HD Wireless Transmission System



Introduction:

- ◆ Professional WHDI(MIMO/OFDM) technology
- ◆ Uncompressed HDMI wireless transmission
- ◆ 2-ch HDMI embedded audio transmission
- ◆ Approx. 200m (LOS) effective transmission distance
- ◆ Less than 1 ms latency
- ◆ 5.1-5.9GHz license free operation frequency
- ◆ AES 128bit encryption
- ◆ Compact designed transmitter, ideal for HDV camera
- ◆ SDI output via receiver

Specifications:

Model	S-4913R	S-4913T
Input	HDMI input x1	Wireless receiving
Output	Wireless transmitting	3G/HD-SDI output x2
	HDMI input	SDI output
Video format	1080P (60 / 59.94 / 50)	Same as input format
	1080i (60 / 59.94 / 50)	
	1080p (30 / 29.97 / 25 / 24 / 23.98)	
	1080psf (30 / 29.97 / 25 / 24 / 23.98)	
	720p (60 / 59.94 / 50)	
Wireless frequency	5.1-5.9GHz License-free	
Radio modules	OFDM	
Transmission distance	≥200m	
Latency	≤1ms	
Power consumption	≤10W	
Radio power	≤63mW	
Input voltage	DC 7-17V	DC 8-17V
Working environment	Temperature: 0°C +40°C, Humidity:10%-95%	
Dimension (with antenna)	71×270×28mm	143×344×58mm
Net weight	256g (with antenna)	655g (with antenna)



S-4913T
Transmitter



S-4913R
Receiver

SWIT Electronics Co., Ltd.

Web: www.swit.cc

Email: contact@swit.cc

Tel: +86 25 85805753

Fax: +86 25 85805296

Distributed by: