

Preliminary Catalogue



CA-70HDT(X)
Camera Adapter


World's First

Budget Oriented
HD -Triax/Coax Camera Adatper



BU-70HDT(X)
Base Unit

The CA-70HD camera adapter plugs directly into the camera's battery mount and allows broadcasters to convert their ENG camera into a studio configuration. No delay in mainstream signal process, HD SDI high quality In/Out. Integrated with standard camera mounts either Antom Bauer or V-Mount.



Specifications

Base Unit (BU-70HD)

Video

HD/SD SDI Uncompressed	BNC x 2, SMPTE 292M (1.5 Gb/s) or SMPTE 259M (270 Mb/s), 0.8 Vp-p, 75Ω
Return Program Video (Analogue Composite)	BNC x 1, *Composite Video In
Gen Lock In (Composite Video / Black Burst)	BNC x 1, 1.0Vp-p, 75Ω
Camera Set Up Video Out	BNC x 1, 1.0Vp-p, 75Ω (*Composite Video Out)

Audio

Return Program Audio (In)	Balanced Audio In
Audio Out (Analog)	Balanced Audio Out
HD SDI (Embedded)	HD/SDI De-embedded module as option
Intercom	Two way 4 wire balanced or 3 wire unbalanced In/Out

Control & Others

Tally In	Tally In 9 Pin Connector
TC Out	BNC x 1, Low impedance, 2.0 ±0.5V p-p
Camera Remote Control Data	8/10 pin Camera Remote Control Connector (Change as per camera models), Visit our website.

Power

Power In	AC 100~220V, 50/60 HZ, Approx. 90W
----------	------------------------------------

CAMERA ADAPTER (CA-70HD)

Video

HD/SD SDI Uncompressed	BNC x 2, SMPTE 292M (1.5 Gb/s) or SMPTE 259M (270 Mb/s), 0.8 Vp-p, 75Ω
Return Program Video (Analogue Composite)	BNC x 1, *Composite Video Out
Gen Lock Out (Composite Sync)	BNC x 1, 1.0Vp-p, 75Ω
Camera Set Up Video Out	BNC x 1, 1.0Vp-p, 75Ω (*Composite Video Out)

Audio

Return Program Audio (Out)	Audio Out
Audio In (Analog)	Balanced Audio In
HD SDI (Embedded)	HD/SDI De-embedded module as option
Intercom	Two way 4 wire balanced or 3 wire unbalanced In/Out

Control & Others

Tally Out	Tally Out 12 Pin Connector
TC Out	BNC x 1, Low impedance, 2.0 ±0.5V p-p
Camera Remote Control Data	8/10 pin Camera Remote Control Connector (Change as per camera models), Visit our website.

Power

Power In (Camera Power)	DC 32V supplied through Triax/Coax Cable from Base Unit to Camera Adapter
-------------------------	---

* Composite Video Out is provided for monitoring purpose, not recommended for transmission.

Agent / Distributor

STUDIO PLUS

Sales: enquiry@studioplusbroadcast.com
 Distributor: agnespinto@studioplusbroadcast.com
 Technical: robinhood@studioplusbroadcast.com
 Tel: +97150 6465332
<http://www.studioplusbroadcast.com>

SUNS CORPORATION, JAPAN

<http://www.suns-corp.com>