



Camera Accessories    Others

## LUMIX Accessory DMW-YAGHE

POWER		Power source	12 V DC, 1.5A (including a digital camera)
OPERATING ENVIRONMENT		Operating temperature	0°C to 40°C (32°F to 104°F)
		Operating humidity	10% to 80% (no condensation)
DIMENSIONS / WEIGHT		Weight	Approx. 750 g / 24.46 oz (main unit only)
		Dimensions (W x H x D)	160 x 64 x 91 mm / 6.30 x 2.52 x 3.58 in (excluding protrusions and HDMI terminal)
VIDEO (DIGITAL VIDEO)	Resolution	Cinema4K	4096 x 2160 [24p]
		QFHD	3840 x 2160 [29.97p]/3840 x 2160 [25p]/3840 x 2160 [24p]/3840 x 2160 [23.98p]
		FHD	1920 x 1080 [59.94p] (3G-SDI Level-A/B)/1920 x 1080 [50p] (3G-SDI Level-A/B)/1920 x 1080 [59.94i]/1920 x 1080 [50i]/1920 x 1080 [29.97PsF]/1920 x 1080 [25PsF]/1920 x 1080 [24PsF]/1920 x 1080 [23.98PsF]
		HD	1280 x 720 [59.94p]/1280 x 720 [50p]
	Color sampling	Y:Cb:Cr=4:2:2	
Bit depth	8 bits / 10 bits		
AUDIO (DIGITAL AUDIO)		Sampling frequencies	48 kHz (synchronized with video)
		Audio quantization	16 bit
		Headroom	12 dB
INPUT / OUTPUT		TC IN	BNC x 1, 1.0-4.0 V [p-p], 10 kΩ
		AUDIO IN [CH1, CH2]	XLR (3-pin) x 2, High impedance,/LINE / MIC / +48 V (switchable)/LINE: 0 dBu/MIC: -50 dBu/+48 V: Phantom +48 V compatible, -50 dBu
		SDI OUT [1, 2, 3, 4]	BNC x 4, 0.8 V [p-p], 75 kΩ/Embedded audio: 2 channel, embedded timecode
		HDMI OUT	HDMI type A (VIERA link not supported), 2 channels (linear PCM)

Copyright © 2014 Panasonic UK & Ireland