

SONY®

NTSC/PAL

DVCAM™



Digital Camcorder **DSR-PDX10** **DSR-PDX10P**

A new addition to the DVCAM™ camcorder family, the DSR-PDX10/PDX10P, with its 3-CCD MEGA-pixel camera system provides you with superb picture quality. Its compact design and sophisticated new features, such as an MPEG Movie function and a USB port offers innovation to your shooting styles and productions.

Camera Features

- ▶ 1/4.7-inch type MEGA-pixel 3-CCD Camera System
- ▶ Advanced HAD™ CCD Technology
- ▶ 530 lines of horizontal resolution
- ▶ 12x Optical zoom/ 48x Precision digital zoom
- ▶ 14-bit DXP(Digital Extended Processor)
- ▶ Manual Focus Ring
- ▶ Program A/E
- ▶ Custom Presets (Color level, sharpness, white balance shift, AGC limit, A/E shift)
- ▶ Touch Panel Operation (Spot Focus/ Spot AE)



Touch Panel LCD Monitor

VTR Features

- ▶ Recording capability in DVCAM or DV (SP mode) format.*1
- ▶ Playback capability of DVCAM or DV (SP mode) recorded tapes
- ▶ i.LINK™ *2 (DV) interface
- ▶ Analog audio/video Input (Composite, S-video)
- ▶ Remote (LANC)

Convenient Features

- ▶ USB streaming - The DSR-PDX10 is capable of streaming video and audio via its USB port. In CAMERA mode, video and audio are captured and converted to motion JPEG signals in real-time and subsequently streamed. Similarly in VCR mode, the playback signal is converted to motion JPEG and streamed through the USB port.
- ▶ Integrated Memory Stick™ IC recording media Slot
- ▶ MPEG Movie recording up to 85mins. on a 128 MB Memory Stick *3
- ▶ Editing to an MPEG Movie from a DV/ DVCAM tape is possible.
- ▶ Still picture recording*4 (640x480/ 1,152 x 864 dot)
- ▶ Progressive Shutter System (Still Picture only)
- ▶ XLR 2-ch Adaptor/Intelligent Accessory Shoe
- ▶ 3.5-inch type 246,000 dot Precision Color LCD Monitor*5
- ▶ 180,000 dot Precision Black & White LCD Viewfinder
- ▶ Super SteadyShot™ (Optical)
- ▶ TC/User bit preset capability
- ▶ Digital Program Editing*6 allows auto-assemble-like editing without an edit controller.
- ▶ AV to DV Out (For converting analog input signals to DV signals)
- ▶ InfoLITHIUM™ "M series" Battery System



MEMORY STICK™



XLR 2-ch Audio Input Adaptor (terminal)



XLR 2-ch Audio Input Adaptor (Select Switch)

Preliminary

*1 When recording in DV (SP) format, transitions between cut to cut may not be smooth. In addition, when the recording format is switched between DVCAM and DV, the transition may not be recorded smoothly.

*2 i.LINK is a Sony trademark used only to designate that a product is equipped with an IEEE 1394 connector. i.LINK stands for IEEE 1394-1995 standards and their revisions.  is the logo for products that implement i.LINK. All products with an i.LINK connector may not communicate with each other. Please refer to the documentation that comes with any device having an i.LINK connector for information on compatibility, operating conditions, and proper connection.

*3 Available storage capacity may vary and a portion of the memory is used for data management functions.

*4 The still picture file is not compatible with DSR-PD100.

*5 Viewable area measured diagonally

*6 Frame accuracy is not guaranteed.

DSR-PDX10/PDX10P Specifications

Lens	12.1 Variable speed zoom lens F-3.6 to 43.2 mm; Filter Diameter 37 mm
Focus	Auto/Manual (ring)/Infinity/One push auto
Imaging Device	Three 1/4.7-inch type CCDs, 1,070,000 pixels (gross)
White Balance	Auto/One-push/Out door (5800 K)/Indoor (3200 K)
Shutter speed	1/4 to 1/10000 (NTSC), 1/3 to 1/10000 (PAL)
Exposure	Auto/Manual
Minimum Illumination	7 lx
Horizontal Resolution	530TV lines
Viewfinder	180,000 dot Black & White LCD, Zebra Pattern
Audio Signal	Rec 48kHz/16-bit, 32kHz/12bit Play 48kHz/16-bit, 32kHz/12-bit, 32kHz/16-bit, 44.1kHz/16-bit
Built-in Speaker	Dynamic Speaker
LCD	TFT Active Matrix, 3.5-inch type, 246,000 dots
Tape Speed	Approx. 28.2 mm/s (DVCAM mode) Approx. 18.8 mm/s (DV SP mode)
Maximum Recording Time	40 minutes(DVCAM mode) 60 minutes(DV SP mode, with PDVM-40ME)
Video Signal	EIA Standard, NTSC color system (DSR-PDX10) CCIR Standard, PAL color system (DSR-PDX10P)


Connectors	
Audio(LINE)/Video IN/OUT	AV-mini jack x1
S-video IN/OUT	Mini-DIN 4-pin jack x1
MIC IN	Stereo mini jack x1
i.LINK IN/OUT	4-pin jack x1
Headphone	Stereo mini jack x1
LANC	Stereo mini-mini jack x1
DC IN	8.4V for AC-L10 AC adaptor x1
USB	Mini-B x1
(XLR Audio adaptor)	
Audio IN	XLR 3-pin female x2 (LINE/MIC/MIC+ATT.) +48 V (ON/OFF)
Operating Temperature	0 to 40°C
Storage Temperature	-20 to 60°C
Power Requirements	DC 7.2 V (Battery), DC 8.4 V (AC adaptor)

Supplied Accessories

ECM-NV1 Monaural Microphone
AC-L10 AC Adaptor
NP-FM50 InfoLITHIUM Rechargeable Battery Pack
RMT-811 Remote Commander and R6 Batteries (x2)
MSA-8A IC Recording Media "Memory Stick"

USB Cable
Image Mixer / USB Driver software CD-ROM
Stereo AV Cable
Lens Hood
Hood Cap

Optional Accessories

 ECM-670 Electret Condenser Microphone ECM-670 ECM-672	 CAC-12 Microphone Holder	 EC-0.3C2 Microphone Cable EC-0.3C2 EC-0.5C2	 NP-QM91 InfoLITHIUM Rechargeable Battery Pack NP-QM91/NP-QM71/NP-FM50
 AC-SQ950D AC/DC Adaptor/Charger	 MSA-64A Memory Stick MSA-16A (16MB) MSA-32A (32MB) MSA-64A (64MB) MSA-128A (128MB)	 VMC-IL4415 i.LINK Cable VMC-IL4408A (0.8m, 4-pin to 4-pin) VMC-IL4415 (1.5m, 4-pin to 4-pin) VMC-IL4435 (3.5m, 4-pin to 4-pin) VMC-IL4615 (1.5m, 4-pin to 6-pin) VMC-IL4635 (3.5m, 4-pin to 6-pin) CCFD-3L (3m, 4pin-6pin with lock)	 HVL-FH1100 Flash HVL-FH1100 Video Flash Light HVL-FDH4 Video Light HVL-S3D Video Flash HVL-F10
 VCL-HG0737X Wide Conversion Lens VCL-HG0737X Wide End Conversion Lens VCL-MHG07A Teleconversion Lens VCL-HG2037X	 LCH-TRV950 Hard Carrying Case	 VF-R37K ND Filter and Protector VF-R37K PL Filter and MC Protector VF-37CPKS	

©2002 Sony Corporation. All rights reserved.
Reproduction in whole or in part without written permission is prohibited.
Features and specifications are subject to change without notice.
All non-metric weights and measures are approximate.
Sony is a registered trademark of Sony Corporation.
Super SteadyShot, Handycam, InfoLITHIUM are trademarks of Sony Corporation.
DVCAM, i.LINK, Memory Stick and their respective logos are trademarks of Sony Corporation.