

The convenience of touch panel monitors makes them a practical choice for places like hospitals, factories, reception areas and retail shops. EIZO touch panel monitors offer superior color and clarity, and feature slim bezels on the top and sides to save space on the desk or counter. Finger touch is standard, with pen touch available when using the optional TP1 dedicated touch pen. EIZO offers a wide range of models to meet your specific requirements.



19" L760T-C
Touch Panel Color LCD Monitor

FEATURES

Analog Capacitive Screen

An analog capacitive panel provides fast touch response, extremely long touch life (minimum 225 million touches), and high optical clarity for performance and longevity.

Communications Protocol

The L760T-C, L362T, and L352T-C offer a touch interface through an RS-232 serial port, and the L560T-C, L363T-C, and L353T-C through a USB port.

High Image Quality

These high performance touch panels feature excellent contrast ratio and brightness, displaying vivid colors and sharp, clear images. Their viewing angles are wide (178° for the L760T-C and L560T-C), with minimal color shift when viewed from the side. An anti-bacterial treatment on the touch panel surface prevents annoying screen reflections.

Brightness Stabilization

At startup or upon wakeup, an EIZO-patented drift correction function quickly stabilizes the brightness level. In addition, a sensor measures the backlight brightness and compensates for brightness fluctua-

tions caused by the ambient temperature and the passage of time.

Digital and Analog Inputs

With both DVI-D and D-Sub mini 15-pin inputs, you can use a computer that has either a digital or an analog graphics board (or both if connected to two computers), and quickly switch between the inputs via a front panel button.

Auto Adjustment

Pressing a button on the front panel automatically adjusts four basic monitor parameters: clock pulse, phase, screen position and resolution.

sRGB Mode

Sets the monitor to the international sRGB color space, for color matching with applications and peripherals like scanners, printers and digital cameras.

Versatile Positioning

Position the screen wherever you like with 82 mm height adjustment, 40° tilt, 70° swivel, and 90° pivot



17" L560T-C
Touch Panel Color LCD Monitor



15" L363T-C
Touch Panel Color LCD Monitors
(L362T, L353T-C & L352T-C 15" models not shown)

for portrait mode (FlexScan L760T-C and L560T-C only). The power supply is built in, so there is no separate power brick or cord. All models comply with VESA mounting standards so the panel can be removed from the stand and placed on a movable arm or wall bracket.

Detailed Image Control

This function offers independent control of hue, saturation, and gain, and adjustment of color temperature in 500 K increments from 4,000 to 10,000 K (including 9,300 K) for accurate, natural display of color.

Touch Panel Pointer

For factories or other environments where gloves are required, the dedicated TP1 touch pen is available.



Product Information Display

The model name, serial number, and total usage time are all accessible in the OSD menu.

Customer Assurance

The monitors meet the strictest medical, safety and EMC emission standards, including TÜV/GM, CE and UL2601-1. They also conform to EIZO's own strict Eco Products 2004 and 2002 environmental criteria for design, manufacture, packaging and usage, including the introduction of lead-free solder and chrome-free steel plates.





FlexScan L363T-C
FlexScan L362T



FlexScan L353T-C
FlexScan L352T-C

38 cm (15") TFT color LCD panel	38 cm (15") TFT color LCD panel
170°, 170° (at contrast ratio of 10:1)	160°, 150° (at contrast ratio of 5:1)
180 cd/m ² / 400:1	180 cd/m ² / 450:1
55 ms (typical)	25 ms (typical)
1024 × 768	1024 × 768
304 × 228 mm	304 × 228 mm
Diagonal: 380 mm	Diagonal: 380 mm
0.297 × 0.297 mm	0.297 × 0.297 mm
16.77 million	16.77 million
Gray, Black	Gray, Black
Analog: 79 MHz, Digital: 66 MHz	Analog: 79 MHz, Digital: 66 MHz
24 – 61 kHz, 55 – 75 Hz	24 – 61 kHz, 55 – 75 Hz
31 – 49 kHz, 59 – 61 Hz (VGA Text: 70 Hz)	31 – 49 kHz, 59 – 61 Hz (VGA Text: 70 Hz)
Analog: RGB Analog, Digital: DVI Standard 1.0	Analog: RGB Analog, Digital: DVI Standard 1.0
D-Sub mini 15 pin, DVI-D 24 pin (switchable)	D-Sub mini 15 pin, DVI-D 24 pin (switchable)
VESA DDC 2B	VESA DDC 2B
AC 100 – 120 V, 200 – 240 V: 50 / 60 Hz	AC 100 – 120 V, 200 – 240 V: 50 / 60 Hz
40 W (maximum)	35 W (maximum)
Less than 3 W	Less than 3 W
–	–
30° Up, 3° Down / –	30° Up, 3° Down / –
With Stand: 346 × 369 × 157 mm Without Stand: 346 × 301 × 54.5 mm	With Stand: 346 × 369 × 157 mm Without Stand: 346 × 301 × 54.5 mm
With Stand: 5.0 kg, Without Stand: 4.1 kg	With Stand: 5.0 kg, Without Stand: 4.1 kg
Auto Brightness Stabilization	Auto Brightness Stabilization
Auto Adjustment, Range Adjustment	Auto Adjustment, Range Adjustment
sRGB, Custom	sRGB, Custom
Clock, Phase, Position, Brightness, Smoothing (5 stages)	Clock, Phase, Position, Brightness, Smoothing (5 stages)
Range Adjustment (RGB), Gamma, Temperature (14 stages: in 500 K increments from 4,000 K – 10,000 K including 9,300 K), Saturation, Hue, Gain, Reset	Range Adjustment (RGB), Gamma, Temperature (14 stages: in 500 K increments from 4,000 K – 10,000 K including 9,300 K), Saturation, Hue, Gain, Reset
VESA DPMS, Off Timer	VESA DPMS, Off Timer
DVI DMPM, Off Timer	DVI DMPM, Off Timer
Signal Settings, VGA Selection, Signal Switching, Product Information (product name, serial number, operating time), OSD Menu Settings, Adjustment Lock, Languages (English, French, German, Italian, Japanese, Spanish, Swedish)	Signal Settings, VGA Selection, Signal Switching, Product Information (product name, serial number, operating time), OSD Menu Settings, Adjustment Lock, Languages (English, French, German, Italian, Japanese, Spanish, Swedish)
Dual 1 W built-in speakers, input/headphone jacks	Dual 1 W built-in speakers, input/headphone jacks
TÜV/GM (EN60601-1), c-Tick, CE Medical Device Directive, CB (IEC60601-1), cTUVus (UL2601-1, CSA C22.2 No. 601-1), FCC-B, Canadian ICES-003-B, VCCI-B, EPA ENERGY STAR®, CCC, EIZO Eco Products 2002 (L362T), EIZO Eco Products 2004 (L363T-C)	TÜV/GM (EN60601-1), c-Tick, CE Medical Device Directive, CB (IEC60601-1), cTUVus (UL2601-1, CSA C22.2 No. 601-1), FCC-B, Canadian ICES-003-B, VCCI-B, EPA ENERGY STAR®, CCC, EIZO Eco Products 2002 (L352T-C), EIZO Eco Products 2004 (L353T-C)
Three Years	Three Years
Analog Capacitive (finger touch)	Analog Capacitive (finger touch)
84%	84%
225 million touches (minimum)	225 million touches (minimum)
Windows 2000 / XP	Windows 2000 / XP
L362T: RS-232C, L363T-C: USB	L352T: RS-232C, L353T-C: USB