



**MD 431 II Speech and Broadcasting Microphone**

By virtue of its design and features, the MD 431 II ranks amongst Sennheiser’s most exceptional microphones and is suitable for vocal, speech and broadcasting applications. Color: black, sound inlet basket: refined steel. Internal electronics eliminates proximity effect.

**Features—Benefits**

- Exceptionally good feedback rejection
- Shock mounted capsule—low sensitivity to handling noise
- Hum compensating coil—reduces electrical interference
- Integral pop filter
- On/off switch (reed switch) can be locked in the ‘on’ position if required
- Consistent polar pattern and proximity compensating electronics—excellent tonal consistency
- Excellent for voice recognition

**Technical Data**

Pick-up pattern	super-cardioid
Frequency response	40–16,000 Hz
Sensitivity (free field, no load) (1 kHz)	2 mV/Pa ± 3 dB
Nominal impedance	250 Ω
Min. terminating impedance	1 k
Dimensions in inches	1.92 x 7.87
Weight	approx. 8.8 oz

**Optional Accessories**

Foam windshield	MZW 4032
21' XLR microphone cable	MC21N
Stand adapter (included)	MZR 4032

**Supplied Accessories**

1 Quick release stand adapter	MZA 4031
-------------------------------	----------

**Architect’s Specifications**

Super-cardioid stage microphone, hum compensating coil, integral popshield, reed on/off switch, frequency response 40–16,000 Hz, sensitivity (free field, no load) 2 mV/Pa ± 3 dB at 1 kHz, nominal impedance 250 Ω, min. terminating impedance 1 k, dimensions in inches: 1.92 x 7.87, body 1.22 inches, weight approx. 8.8 oz.