

Pre-read Editing Control Unit

RM-G820E

64

- Controls D-9 Pre-Read: A/B Roll Editing and Layering Using Only Two Machines
- RS-422A Interface
- Multi-Event Editing Max. 99 events with Renumber and Ripple (EDL manage) function
- Variable Motion Control (VMC) editing and Motion Memory Editing (Max. 7 events) with BR-S525E and D-9
- Time Code (EBU LTC & VITC) and CTL Based Editing Capability
- Audio Split Editing
- Four Variable Timing GPI (General Purpose Interface) Outputs
- Audio Monitor Level Control
- Multi Purpose LCD display



Power requirement:	DC 9 V
Power consumption:	8 W
Weight:	4.8 kg (10.6 lbs)
Dimensions (W × H × D):	430 × 99 × 311 mm
Operating temperature:	5°C to 40°C
Storage temperature:	-20°C to 60°C
Operating humidity:	30% to 80%
VCR control functions:	PLAY, FF, REW, STOP, PAUSE/STILL, SHUTTLE SEARCH, JOG, EJECT, REC EE, REC
Editing control functions:	Edit modes: Assemble and insert
Reference signals:	EBU time code, CTL time code or CTL pulse
Capstan bump:	ON/OFF (independent)
Editing accuracy:	Timecode-referenced in capstan bump mode: ±0 frame (depending on VCR) CTL-referenced in capstan bump mode: ±2 frames (depending on VCR)
Memory capacity:	99 events

VCR interface:	RS-422A (9-pin)
Preroll time:	5, 7 or 10 sec.
Number of VCRs controllable:	1 player and 1 recorder
Time counter	
Counter reading display:	Up to 23 hours, 59 minutes, 59 seconds, 24 frames (TC/CTL 24-hour display) from -9 hours, 59 minutes, 59 seconds, 24 frames (CTL 10-hour display)
Total programme time display:	Maximum 11 hours, 59 minutes, 59 seconds, 24 frames
Accessories:	AC adaptor, Power cord

Optional Accessories

VG-G9050U
9-pin Remote Control Cable (5m/16 ft.)



SA-K66U
Rack Mount Adapter



SA-K80U
10 Numerical/Function Keypad

