

Colour Monitors

TM-1700PN 17" PAL/NTSC



TM-2100PN 21" PAL/NTSC



TM-1700PN:

- High 550 Horizontal TV lines resolution picture from unique 17 inch CRT
- Vertical Stripe phosphors
- 16:9 or 4:3 selectable aspect ratio
- Brightness peak suppression system reduces tube wear
- PAL/NTSC auto selection
- Built-in speaker
- User-friendly on-screen display menu
- Memory function
- Control lock
- Wired remote control
- Rugged metal cabinet
- Optional RK-1700E rack mount

Type	Colour video monitor
Colour system	PAL/NTSC, Auto select
CRT	17" diagonal, in-line guns, stripe pitch of 0.42 mm
Horizontal resolution	550 TV lines
Colour temperature	6,500°K / 9,300°K (selectable)
Power requirement	230 V AC, 50/60 Hz
Power consumption	0.6 A
Video Input A: Composite	1.0 VB (p-p), 75 ohms, negative sync, auto-termination, BNC x 2, bridged out possible
Video Input B: Composite	1.0 VB (p-p), 75 ohms, negative sync, auto-termination, BNC x 2, bridged out possible
Video Input B: Y/C	Y: 1.0 V (p-p), 75 ohms, negative sync C: 0.286 V (p-p), 75 ohms (NTSC) C: 0.3 V (p-p), 75 ohms (PAL) Auto termination, DIN 4-pin x 2, bridged out possible
Audio input / output	RCA pin x 4 for input A and input B channels, bridged out possible
Audio output power	1 W
Power cord	Continental type (TM-1700PN) UK mains lead type (TM-1700PN-K)
Remote terminal	RCA pin x 2, bridged out possible
Dimensions	395 (W) x 334.3 (H) x 420.5 (D) mm (14-1/4" x 13-1/4" x 15-1/2")
Weight	17.2 kg

TM-2100PN:

- 450 Horizontal TV lines resolution picture from 21 inch CRT
- Vertical Stripe phosphors
- 16:9 or 4:3 selectable aspect ratio
- Brightness peak suppression system extends tube life
- PAL/NTSC auto selection
- Built-in speaker
- User-friendly on-screen graphical menu
- Memory function
- Control lock
- Wired remote control
- Rugged metal cabinet

Type	Colour video monitor
Colour system	PAL/NTSC, Auto select
CRT	21" diagonal, in-line guns, stripe pitch of 0.69 mm
Horizontal resolution	450 TV lines
Colour temperature	6,500°K / 9,300°K (selectable)
Power requirement	230 V AC, 50/60 Hz
Power consumption	MAX 0.72 A
Video Input A: Composite	1.0 VB (p-p), 75 ohms, negative sync, auto-termination, BNC x 2, bridged out possible
Video Input B: Composite	1.0 VB (p-p), 75 ohms, negative sync, auto-termination, BNC x 2, bridged out possible
Video Input B: Y/C	Y: 1.0 V (p-p), 75 ohms, negative sync C: 0.3 V (p-p), 75 ohms (PAL) C: 0.286 V (p-p), 75 ohms (NTSC) Auto termination, DIN 4-pin x 2, bridged out possible
Audio input / output	RCA pin x 4 for input A and input B channels, bridged out possible
Audio output power	1 W
Remote terminal	RCA pin x 2, bridged out possible
Power cord	Continental type (TM-2100PN) UK mains lead type (TM-2100PN-K)
Dimensions	476 (W) x 407.5 (H) x 492 (D) mm (18.-3/4" x 16-1/16" x 19-3/8")
Weight	28.5 kg

All model numbers, specifications and prices are subject to change without notice.