

JVC
PROFESSIONAL

17" HIGH-RESOLUTION COLOR VIDEO
MONITOR

TM-H1700G

High-Resolution, Multi-Purpose Monitor with
Remote Terminal for Multiplex Applications



- High-Resolution Pictures with 750 Horizontal Lines
- Selectable Aspect Ratio: 16:9/4:3
- Underscan Supports Multiplexer Applications
- On-Screen Menu
- Multi-Standard Compatibility: NTSC/PAL
- Universal Power Supply: 120V/230V AC
- EIA Rack Mountable (Height: 9U)
- Big Screen, Small Cabinet Design
- Wired Remote Control
- UL/CE Approved

High-Resolution, Large-Screen, Multi-Purpose, Utility Monitor that's Ideal for Multiplexer Applications

JVC has designed the perfect multi-purpose, utility monitor with its TM-H1700G. Packaged in an ultra-compact, rack-mountable cabinet, the TM-H1700G delivers 750 lines of horizontal resolution on a 17-inch display. Switch over from an aspect ratio of 4:3 to wide-screen 16:9 and it's ideal for a six-picture splitter arrangement. Its Underscan function supports multiplexer applications, and it has a multi-function remote capability for off-site operation. Naturally the TM-H1700G comes with all of the high-end features users have come to expect with the economical monitors, such as on-screen menu-driven parameter setting, NTSC/PAL compatibility, universal power supply, and rugged reliability. All of this from a 17-inch monitor that takes up the same vertical installation space as most of conventional 14-inch monitors.



750 LINES
High-Resolution Monitor

Screen picture simulated

■ 17-inch High-Resolution CRT

The TM-H1700G features a P-22 phosphor 17-inch Full-Square CRT with in-line guns and a trio-dot pitch of 0.27 mm. For the user, that translates into 750 lines of horizontal resolution and a selectable color temperature (6,500°K/9,300°K) for crisp pictures with outstanding color fidelity.

■ Selectable Aspect Ratio: 16:9/4:3

Users can switch over between a standard aspect ratio of 4:3 and a wide-screen ratio of 16:9 with a simple On-screen Menu operation. The wide aspect ratio is especially useful for surveillance applications when using CCTV equipment such as a six-picture splitter.

■ Underscan for Multiplex Operation

When connected to a multiplexer for surveillance applications, the Underscan function of JVC's TM-H1700G eliminates loss and distortion from multi-screen pictures.

■ Wired Remote Control Capability

The TM-H1700G is provided with remote control D-sub 15-pin connector, which allows the user to select and change Aspect Ratio (16:9/4:3), Input, and Underscan.

■ On-Screen Menu for Adjusting Monitor Parameters

Changing monitor parameters couldn't be easier with the TM-H1700G's on-screen menu. Featuring a user-

friendly graphic interface, it guides a user wanting to customize the monitor for individual preferences and applications. Resetting to the default settings is a quick one-touch operation. Adjustable parameters include: Aspect Ratio, Color Temperature, and Video System. Contrast, Brightness, Chroma, and Phase can be adjusted via ergonomically arranged push-buttons on the front panel.

■ Big Screen, Small Cabinet Design

The TM-H1700G benefits from JVC's focus on minimizing cabinet size. The result is that the TM-H1700G is the same height as most of conventional 14-inch models and is little wider. Ruggedly built, the monitor can be mounted in a 9U-high rack using an optional EIA rack mount adapter (RK-C1700E).

■ Multi-Standard Compatibility

The TM-H1700G accepts both NTSC and PAL signals. Its auto-detect function identifies the signal being input and switches mode automatically. To further enhance flexibility the monitor can be connected to either 120V AC or 230V AC power supply sources.

■ Comprehensive Input Terminals

JVC's full-featured TM-H1700G comes with Y/C input terminal (4-pin DIN) with bridged output for S-VHS signals, as well as two composite input terminals (2-channel BNC), each also with a bridged output.





Specifications

Color System	NTSC/PAL
CRT	17" (diagonally measured), trio-dot pitch 0.27 mm P-22 phosphor
Scanning Frequency	f(H) 15.734 kHz (NTSC)/15.625 kHz (PAL) f(V) 59.95/50 Hz
Horizontal Resolution	more than 750 TV lines
Power Requirements	120V AC (UL)/230V AC (CE)
Color Temperature	6,500°K/9,300°K
Input Terminal	Input A Composite Video, BNC x 2, bridged-output possible Input B Composite Video, BNC x 2, bridged-output possible, Y/C priority input, mini DIN 4-pin x 2, bridged-output possible
Remote Terminal	D-sub 15-pin x1, MAKE CONTACT for functions of ■ Input Select ■ Aspect Changeover (16:9/4:3) ■ Underscan
Optional Accessories	EIA Rack Mount Adapter (RK-C1700E)
Dimensions (W x H x D)	15-5/8 x 13-1/4 x 16-1/2 inches 395 x 334 x 418 mm
Weight	43.2 lbs. (19.6 kg)

Dimensions

Unit: inches (mm)



Rack Mount Adapter



RK-C1700E
 ■ EIA Rack Mount Adapter

JVC

VICTOR COMPANY OF JAPAN, LIMITED

DISTRIBUTED BY

Design and specifications subject to change without notice.