



Price: \$399.00

V-LCD5.6-PRO 5.6" LCD Monitor with Audio & Reverse Image

The **V-LCD5.6-PRO** is a 5.6" color monitor with built-in speaker and reverse image capability. The V-LCD5.6-PRO adds a new dimension of clarity in viewing video signals in mobile and fixed monitoring applications. It is equipped with sound, color, contrast and brightness controls. This monitor also has a earphone plug for private sound monitoring. The mirror-image function on this unit makes it ideal for RV's or busses with a camera to view behind while backing up. An optional battery pack (V-BP12-LCD) is available for field use. Rechargeable battery pack can power monitor for up to 1 hr. and 20 mins. Comes complete with built-in tilt stand, adapter cables and power supply. An optional swivel stand is also available separately, (V-LCD4-ST). This unit is also available as a kit with case and rechargeable battery pack, part no. V-LCD5.6-PRO-KIT (Price: \$429.00).



V-LCD5.6-PRO-KIT

The **V-LCD5.6-PRO-KIT** includes the V-LCD5.6-PRO a rechargeable battery pack (with charger) and a handsome nylon carrying case with shoulder strap. The carrying case is designed to hold all the necessary battery pack and cables ready for field use. The rechargeable batter pack will power the unit for 2hrs. continuously. This kit will also include a wall adapter allowing the unit to be used while the battery is being charged.

Price: \$429.00

NEW



Price: \$549.00

V-ASL7000 7" Cable Ready NTSC TV/Monitor

The **V-ASL7000** is Low reflection high resolution TFT LCD/Monitor with Tuner. Features include Cable ready NTSC tuner with Booster interior Rod antenna or CATV feed, 2 channels of Video/Audio input plus switched output of on screen image and audio for routing to another display. Audio can be transmitted to a close proximity FM receiver. There are 5 screen format zoom settings and the image can be inverted for ceiling mount applications. The V-ASL7000 includes User manual, Full function Remote Control, 14 VDC power supply (requires 120 VAC), Mounting Bracket/Pedestal, Video Input cable and RF Cable TV adapter. PAL model also available.

Display (Viewing Area)	6.125" wide x 3.375" high (7" diagonal)
Resolution (Pixels)	1440 Pixel wide x 234 Pixel high (Wide Screen 16:9 aspect ratio)
Signal Input	2 Composite NTSC plus 2 Mono Hi Z Unbalanced Audio
Signal Output	Composite NTSC
FM Transmitter	87.5 to 89.5 MHz
Brightness (in cd/m²)	200 cd/m ²
Contrast Ratio	100:1
Tuner	NTSC VHF/UHF/CATV (125 Channel)
Power required	10 to 16 V D.C. from external supply (included) (1600 mA max)
Dimensions	7.375"W x 4.625"H x 1.0"D
Weight	1.75 lbs



Price: \$949.00

V-LCD8-PRO 7.9" High Resolution TFT LCD Monitor with NTSC/PAL Auto Recognition

Low price and professional performance are the hallmarks of the **V-LCD8-PRO**. With a bright 350 cd/m² screen and sleek design, this 8-inch model is ideal for any indoor or outdoor mobile application. Fixed installation is achieved with a 1/4" screw mount located on the bottom of the unit. Inputs include NTSC/PAL auto recognition for composite and S-Video inputs, both with loop through connections. This model includes our bayonet locking 12 VDC power supply, ensuring that power will not come undone while being handled. There is also a convenient on-screen menu display to access power, color, tint, contrast and brightness controls.

- Plastic cabinet with 1/4" mount for ease of installation
- Bright and vivid color picture
- Slim, portable design
- Low power consumption
- Accepts composite and S-Video, each with active loop through
- NTSC/PAL auto recognition
- Weighs only 1.7 lbs

Display (Viewing Area)	7.9" (6.35"H x 4.65"V)
Resolution (Pixels)	480 H x 234 V
Dot Pitch	0.112 mm x 0.504 mm
Brightness (in cd/m²)	350 cd/m ²
System	NTSC/PAL Auto Recognition
Inputs	1 Composite Video BNC with loop, 1 S-Video with loop
Power required	12 VDC, 3.0 Amp Max
Dimensions	9.41"W x 6.25"H x 1.50"D
Weight	1.7 Lbs