

COMING SOON



Price: \$999.95

V-R70DP 1.2 TFT-Megapixel™ Stand alone Video Assist Monitor

Display (Viewing area)	7" (6.14" x 3.27")
Resolution (Pixels)	800 H x RGB x 480 V
Dot Pitch	0.065 mm x 0.175 mm
Brightness (in cd/m ²)	380 cd/m ²
System	NTSC/PAL auto rec
Inputs per panel (total)	2 Composite, 1 S-Video
Dimensions	7.60"W x 5.16"H x 2.16"D
Approx. Weight	1.8 lbs
Power Consumption	10-17 VDC, 600 mA

Inputs

Composite

S-Video

1.2 TFT MEGAPIXEL

The **V-R70DP** is the successor to the V-R70P. Significant improvements over the previous model include our Completely Digital TFT-Megapixel™ high resolution LCD screen with 1.2 million pixels, V-Mount battery adapter, 4 pin XLR power jack, and optical grade polycarbonate screen protection. Analog signals are digitized using an advanced 10 bit process with 4x over sampling and adaptive 5 line comb filter plus exacting color space conversion. Video is scaled to fit on screen in the highest resolution using a state of the art LSI that incorporates 4 x 4 pixel interpolation with precision Gamma correction to product the best images available.

- Durable metal enclosure
- "V" Mount battery adapter included
- Runs 4 to 6 hours on optional 50WH battery
- High Resolution 7-inch wide screen 800x480 Dots with 1.2 million pixels
- Optical grade polycarbonate screen cover with Antireflective/Antiglare coating
- 100% digital processing
- Analog signals converted to 10 bit digital
- High resolution scaling of all images
- Wide viewing radius - 130° horizontal and 120° vertical provides superior visibility when the viewer is not directly in front of the screen
- 380 candelas per square meter (cd/m²) luminance produces enhanced image quality in varying light and viewing conditions
- 400:1 ratio of contrast between black and white luminance values with response rates less than 30 ms results in excellent quality for moving images
- 4:3 and 16:9 screen aspect ratios
- Automatic NTSC/PAL format detection
- Standard inputs:
 - Composite Video PAL/NTSC with loop output
 - 4 Pin XLR D.C. power jack
- Easy to see three color tally indicators
- Built in Color Bars
- Blue Screen for color adjustment
- Adjustment Settings Memory
- Includes ¼-20 mounting plate that can be attached to any edge of the enclosure (additional mounting plates available)
- Includes universal voltage Class-2 power supply
- Fits into Tektronix® WFM7F05/1700F05 rack adapter
- Optional rack mount kit

COMING SOON



Price: \$1499.00

V-R70P-SD 1.2 TFT-Megapixel™ Stand alone Video Assist Monitor with SDI input

Display (Viewing area)	7" (6.14" x 3.27")
Resolution (Pixels)	800 H x RGB x 480 V
Dot Pitch	0.065 mm x 0.175 mm
Brightness (in cd/m ²)	380 cd/m ²
System	NTSC/PAL auto rec
Inputs per panel (total)	1 Composite, 1 SDI, 1 S-Video
Dimensions	7.60"W x 5.16"H x 2.16"D
Approx. Weight	1.8 lbs
Power Consumption	10-17 VDC, 600 mA

Inputs

Composite

SDI

S-Video

1.2 TFT MEGAPIXEL

The **V-R70P-SD** is the successor to the V-R70-SDI. Significant improvements over the previous model include our Completely Digital TFT-Megapixel™ high resolution LCD screen with 1.2 million pixels, V-Mount battery adapter, 4 pin XLR power jack, and optical grade polycarbonate screen protection. Analog signals are digitized using an advanced 10 bit process with 4x over sampling and adaptive 5 line comb filter plus exacting color space conversion. Video is scaled to fit on screen in the highest resolution using a state of the art LSI that incorporates 4 x 4 pixel interpolation with precision Gamma correction to product the best images available.

- Durable metal enclosure
- "V" Mount battery adapter included
- Runs 4 to 6 hours on optional 50WH battery
- High Resolution 7-inch wide screen 800x480 Dots with 1.2 million pixels
- Optical grade polycarbonate screen cover with Antireflective/Antiglare coating
- 100% digital processing
- Analog signals converted to 10 bit digital
- High resolution scaling of all images
- Wide viewing radius - 130° horizontal and 120° vertical provides superior visibility when the viewer is not directly in front of the screen
- 380 candelas per square meter (cd/m²) luminance produces enhanced image quality in varying light and viewing conditions
- 400:1 ratio of contrast between black and white luminance values with response rates less than 30 ms results in excellent quality for moving images
- 4:3 and 16:9 screen aspect ratios
- Automatic NTSC/PAL format detection
- Standard inputs:
 - SDI (Smpte-259M) with reshaped & relocked output
 - Y/C (S-Video) with loop output
 - Composite Video PAL/NTSC with loop output
 - 4 Pin XLR D.C. power jack
- Easy to see three color tally indicators
- Built in Color Bars
- Blue Screen for color adjustment
- Adjustment Settings Memory
- Includes ¼-20 mounting plate that can be attached to any edge of the enclosure
- Includes universal voltage Class-2 power supply
- Fits into Tektronix® WFM7F05/1700F05 rack adapter
- Optional rack mount kit