

COMING SOON



HDMI
HIGH DEFINITION MULTIMEDIA INTERFACE

HDCP

Price: \$2899.00

V-R72P-2HDA Dual Screen Analog HD/SD monitor set with DVI

Display (Viewing area)	7" (6.14" x 3.27")
Resolution (Pixels)	800 H x RGB x 480 V
Dot Pitch	0.065 mm x 0.175 mm
Brightness (in cd/m ²)	380 cd/m ²
System	NTSC/PAL auto recognition for standard definition signals
Inputs per panel (total)	1(2) Composite, 1(2) S-Video, 1(2) Component HD/SD, 1(2) DVI/HDMI
Dimensions	19.125"W x 5.14"H x 2.5"D
Approx. Weight	5 lbs
Power Consumption	12 VDC, 3.0 Amps

Inputs

- Composite
- S-Video
- Component HD/SD
- DVI/HDMI

180°

Unique 180° Tilt Mechanism

1.2 TFT MEGAPIXEL

The Rack mounted and tiltable **V-R72P-2HDA** represents leading edge technology in LCD/TFT imaging for broadcast and professional video applications featuring High Resolution, 1.2 TFT-Megapixel screens with completely digital signal processing. All SMPTE/ITU analog video standards and signal types plus DVI are accepted and displayed on each screen of this model. Analog signals are digitized using an advanced 10 bit process on each signal path with 4x over sampling and adaptive 5 line comb filter with exacting color space conversion. All video formats are scaled to fit on screen in the highest resolution using a state of the art LSI that incorporates 4 x 4 pixel interpolations with precision Gamma correction to produce the best images available.

- High Resolution 7-inch 1.2 TFT-MegaPixel wide screen
- 100% digital processing
- Analog signals converted to 10 bit digital
- High resolution scaling of all images
- Wide viewing radius - 130° horizontal and 120° vertical provides superior visibility when the viewer is not directly in front of the screen
- 380 candelas per square meter (cd/m²) luminance produces enhanced image quality in varying light and viewing conditions
- 400:1 ratio of contrast between black and white luminance values with response rates less than 30 ms results in excellent quality for moving images
- 4:3 and 16:9 screen aspect ratios for DTV applications in HD and SD formats
- Works with all SMPTE/ITU SDI/HSDSI production formats and frame rates
- Blue Screen for color adjustment
- Internal Color Bar Generator for each screen
- Three lamp tally indicators for each screen
- Ready to mount in 19" rack out of the box
- Front Panel Tilts to achieve optimal viewing
- Standard Multifformat inputs:
 - DVI and HDMI
 - Standard Definition Component Analog
 - Y/C (S-Video)
 - High Definition Component Analog YPrPb
 - Composite Video PAL/NTSC
- Accepts All HD Progressive and Interlace Signals
- Accepts 480P signals
- Loop through of all input signals

COMING SOON



Price: \$4499.00

V-R72P-AFHD Dual Screen Multiformat 1.2 TFT-Megapixel Monitor Set with advanced Functions

Display (Viewing area)	7" (6.14" x 3.27")
Resolution (Pixels)	800 H x RGB x 480 V
Dot Pitch	0.065 mm x 0.175 mm
Brightness (in cd/m ²)	380 cd/m ²
System	NTSC/PAL auto recognition for standard definition signals
Inputs per panel (total)	1(2) Composite, 1(2) S-Video, 1(2) HDSDI/SDI
Dimensions	19.125"W x 5.14"H x 2.5"D
Approx. Weight	5 lbs
Power Consumption	12 VDC, 3.0 Amps

Inputs

- Composite
- S-Video
- HSDSI/SDI

180°

Unique 180° Tilt Mechanism

1.2 TFT MEGAPIXEL

The Rack mounted and tiltable **V-R72P-AFHD** represents leading edge technology in LCD imaging for broadcast and professional video applications featuring High Resolution 1.2 TFT-Megapixel screens with completely digital signal processing. All SMPTE/ITU video standards and signal types are accepted and displayed on each screen of this model. Analog signals are digitized using an advanced 10 bit process on each signal path with 4x over sampling and adaptive 5 line comb filter with exacting color space conversion. All video formats are scaled to fit on screen in the highest resolution using a state of the art LSI that incorporates 4 x 4 pixel interpolations with precision Gamma correction to produce the best images available. Additional features include, setup memory, Zoom function, 6 Frame Marker Overlays, Blue Gun, and direct access for all adjustment and selection functions.

- Two 7-inch 1.2 TFT-MegaPixel wide screens
- 100% digital processing
- Analog signals converted to 10 bit digital
- High resolution scaling of all images
- Wide viewing radius - 130° horizontal and 120° vertical provides superior visibility when the viewer is not directly in front of the screen
- 380 candelas per square meter (cd/m²) luminance produces enhanced image quality in varying light and viewing conditions
- 400:1 ratio of contrast between black and white luminance values with response rates less than 30 ms results in excellent quality for moving images
- 4:3 and 16:9 screen aspect ratios for DTV applications in HD and SD formats
- Works with all SMPTE/ITU SDI/HSDSI production formats and frame rates
- Blue Gun for color adjustment
- Zoom function
- Built in Color Bars
- 6 Frame Marker Overlays with Center Mark
- Adjustment Settings Memory
- Standard Multifformat inputs:
 - HDSDI (all formats)
 - SDI (ITU-R BT601 format)
 - Composite Video PAL/NTSC
 - Loop through of all input signals
- Easy to see three color tally indicators
- Calibrated Color Temperature and Gamma
- Ready to mount in 19" rack out of the box